

# Gutter Mesh



Roofing & Sheetmetal Centre supplies gutter mesh that can be installed over gutters, preventing debris build up and is suitable for a range of roof profiles.

Product feature include:

- Available in aluminium, poly and emberguard
- Match to any roof in up to 22 Colorbond® colours
- Range of widths available, purchase by the metre.
- Bushfire compliant material available
- Installation kits available including mesh, saddle, clips, screws and trims



PRODUCT	FEATURES
Gutter Mesh Poly	660gsm UV stabilised polyethylene diamond mesh with 3.7mm aperture, strand thickness 2mm.
Gutter Mesh Aluminium	Premium grade aluminium designed for Australian conditions. Aperture: 3.5mm (average hole size), strand width 0.7mm
Gutter Mesh Ember	Designed for bushfire prone areas where ember attack may be experienced. With 1.9mm aperture and strand width: 0.5mm. Complies with AS3959-1999/Australian Bushfire Standards.
Tuff Mesh Poly	1000 gsm diamond mesh polyethylene. Suitable for all roofs including galvanised. 3.4mm aperture (average hole size).
Tuff Mesh Ember	Designed for bushfire prone areas subject to heavy ember attack. Ideal for possums, bird and vermin, water tanks, and areas where fine and heavy tree debris falls. 1.6mm aperture (average hole size).
Tuff Mesh Aluminium	Expanded aluminium with a diamond pattern 50% heavier to stop possums, vermin and birds. Highly recommended for valleys, box gutters and new builds, Aperture: 3.4mm (average hole size).

Roofing & Sheetmetal Centre,  
 20 Summit Road,  
 Noble Park North  
 Phone: 9791 5355  
 Email: sales@rscentre.com.au.



[rscentre.com.au](http://rscentre.com.au)